

TRAVEL 90° ±5° AT BOTH ENDS

RATIO 1219.8:1

TURNS TO CLOSE 304.95

MECHANICAL ADVANTAGE ... 346.1 ±10%

MAXIMUM OUTPUT TORQUE (2,500 CYCLES).... 79,100 Nm

MAXIMUM INPUT TORQUE (2,500 CYCLES)..... 228.5 Nm

MOUNTING HOLE DETAIL (BSENISO 5211:2001)

APPROXIMATE WEIGHT 295.8 kg

PREFERRED F48 (12 x M36 on 483 PCD)


MAXIMUM F48 (12 x M36 on 483 PCD)

MINIMUM F25 (8 x M16 on 254 PCD)



OPPERMAN MASTERGEAR

Hambridge Lane, Newbury, Berkshire, RG14 5TS. ENGLAND
Tel: 01635 811500 Fax: 01635 811501 E-Mail: sales@opperman-mastergear.co.uk



DIMENSIONS IN
MM [INCHES]

DATE	11MAY09
DRAWN	GST
CHECKED	DDS
SCALE	1:9

This drawing/design is the property of OPPERMAN MASTERGEAR Ltd. © and must not be used or copied without their specific written consent. Specifications may change without prior notification

DRG No. MF55-F10

REV. A