

OUTPUT KEYWAY DETAILS SHOWN IN OPEN POSITION

	<u>CAPSTAN TYPE HANDWHEEL</u>
	REFERENCE - C4-24
	DIAMETER - 24"(600mm)
	OVER SPOKE - 32"(800mm)

TRAVEL	90° ±5° AT BOTH ENDS	MECHANICAL ADVANTAGE.....	13.8 ± 10%
RATIO	42:1	MAXIMUM OUTPUT TORQUE(1000 Cycles)....	10600 lb.ins.
TURNS TO CLOSE	10.5	MAXIMUM INPUT TORQUE.....	770 lb.ins.


MOUNTING HOLE DETAIL (BSENISO 5211:2001)

PREFERRED	F12 (4 x M12 ON 4.92" PCD)	APPROXIMATE WEIGHT	36.5 lb.
MAXIMUM	F14 (4 x M16 ON 5.51" PCD)		
MINIMUM	F10 (4 x M10 ON 4.01" PCD)		



OPPERMAN MASTERGEAR

Hambridge Lane, Newbury, Berkshire, RG14 5TS. ENGLAND
Tel: 01635 811500 Fax: 01635 811501 E-Mail: sales@opperman-mastergear.co.uk



DIMENSIONS IN INCHES [mm]

DATE	19Aug08
DRAWN	PAB
CHECKED	
SCALE	1:4

This drawing/design is the property of OPPERMAN MASTERGEAR Ltd. © and must not be used or copied without their specific written consent. Specifications may change without prior notification

DRG No. ME-16157-imp

REV. B