

TRAVEL .....	90° ±5° AT BOTH ENDS	MECHANICAL ADVANTAGE .....	188.7± 10%
RATIO .....	615:1	MAXIMUM OUTPUT TORQUE(1000 Cycles).....	24000 Nm
TURNS TO CLOSE .....	153.75	MAXIMUM INPUT TORQUE .....	127 Nm


MOUNTING HOLE DETAIL (BSENISO 5211:2001)

PREFERRED .....	F40 ( 8 x M36 ON 406 PCD)	APPROXIMATE WEIGHT .....	254 kg
MAXIMUM .....	F40 ( 8 x M36 ON 406 PCD) (OR 8 x M30 ON 440 PCD)		
MINIMUM .....	F25 ( 8 x M16 ON 254 PCD)		



**OPPERMAN MASTERGEAR**

Hambridge Lane, Newbury, Berkshire, RG14 5TS. ENGLAND  
 Tel: 01635 811500 Fax: 01635 811501 E-Mail: sales@opperman-mastergear.co.uk



DIMENSIONS IN MM [INCHES]	DATE	07Aug08
	DRAWN	PAB
	CHECKED	
	SCALE	1:7

This drawing/design is the property of OPPERMAN MASTERGEAR Ltd. © and must not be used or copied without their specific written consent. Specifications may change without prior notification

DRG No.	ME-16165	REV.	B
---------	----------	------	---