

GENERAL INFORMATION


TRAVEL $90^\circ \pm 5^\circ$ AT BOTH ENDS
 RATIO 40:1
 TURNS TO CLOSE 10
 MECHANICAL ADVANTAGE ... $11.0 \pm 10\%$

MAXIMUM OUTPUT TORQUE (1000 CYCLES)..... 600 Nm
 MAXIMUM OUTPUT TORQUE (5000 CYCLES)..... 500 Nm
 MAXIMUM INPUT TORQUE (1000 CYCLES)..... 54.5 Nm
 MAXIMUM INPUT TORQUE (5000 CYCLES)..... 45.5 Nm

PREFERRED MOUNTING HOLE DETAIL (BSENISO 5211:2001)
 F12 (4 x M12 on 125 PCD)
 F14 (4 x M16 on 140 PCD)

APPROXIMATE WEIGHT 5.6 kg

 **OPPERMAN MASTERGEAR**
 Hambridge Road, Newbury, Berkshire, RG14 5TS. ENGLAND
 Tel: 01635 811500 Fax: 01635 811501 E-Mail: sales@opperman-mastergear.co.uk

 To BS308
 DIMENSIONS IN MM [INCHES]

| | |
|---------|---------|
| DATE | 10Feb05 |
| DRAWN | BJB |
| CHECKED | PAB |
| SCALE | 1:2 |