

BASIC PARTS BUILD No. N/A

TRAVEL ..... 90° ±5° AT BOTH ENDS  
 RATIO ..... 42:1  
 TURNS TO CLOSE ... 10.5

MECHANICAL ADVANTAGE ..... 11.3 ±10%  
 MAXIMUM OUTPUT TORQUE .... 1000 Nm  
 MAXIMUM INPUT TORQUE ..... 88.5 Nm

MOUNTING HOLE DETAIL (ISO 5211)


PREFERRED ..... F12 (4 x M12 on 125 PCD)  
 MAXIMUM ..... F14 (4 x M16 on 140 PCD)  
 MINIMUM ..... F10 (4 x M10 on 102 PCD)

APPROXIMATE WEIGHT ..... 12 kg



**OPPERMAN MASTERGEAR**

Hambridge Road, Newbury, Berkshire, RG14 5TS. ENGLAND  
 Tel: 01635 811500 Fax: 01635 811501 E-Mail: mastergear@oml.co.uk



DIMENSIONS IN  
 MM [INCHES]

DATE	17JAN02
DRAWN	JDH
CHECKED	PAB
SCALE	1:2.5

This drawing/design is the property of OPPERMAN MASTERGEAR Ltd. © and must not be used or copied without their specific written consent

DRG No. ME-15355

REV. A