

BASIC PARTS BUILD No. N/A

TRAVEL ..... 90° ±5° AT BOTH ENDS  
 RATIO ..... 88:1  
 TURNS TO CLOSE ... 22

MECHANICAL ADVANTAGE ..... 26.5 ±10%  
 MAXIMUM OUTPUT TORQUE .... 4500 Nm  
 MAXIMUM INPUT TORQUE ..... 170 Nm

MOUNTING HOLE DETAIL (ISO 5211)


PREFERRED ..... F16 (4 x M20 on 165 PCD)  
 MAXIMUM ..... F25 (8 x M16 on 254 PCD)  
 MINIMUM ..... F16

APPROXIMATE WEIGHT ..... 45 kg



**OPPERMAN MASTERGEAR**

Hambridge Road, Newbury, Berkshire, RG14 5TS. ENGLAND  
 Tel: 01635 811500 Fax: 01635 811501 E-Mail: mastergear@oml.co.uk



To BS308

DIMENSIONS  
 IN  
 MM [INCHES]

DATE  
 DRAWN  
 CHECKED  
 SCALE

18JAN02  
 JDH  
 PAB  
 1:5

This drawing/design is the property of OPPERMAN MASTERGEAR Ltd. © and must not be used or copied without their specific written consent

DRG No. ME-15363

REV. A