

BASIC PARTS BUILD No. N/A

TRAVEL .....  $90^\circ \pm 5^\circ$  AT BOTH ENDS  
RATIO ..... 88:1  
TURNS TO CLOSE ... 22

MECHANICAL ADVANTAGE .....  $26.5 \pm 10\%$   
MAXIMUM OUTPUT TORQUE .... 4500 Nm  
MAXIMUM INPUT TORQUE ..... 170 Nm

MOUNTING HOLE DETAIL (ISO 5211)


PREFERRED ..... F16 (4 x M20 on 165 PCD)  
MAXIMUM ..... F25 (8 x M16 on 254 PCD)  
MINIMUM ..... F16

APPROXIMATE WEIGHT ..... 48.5



**OPPERMAN MASTERGEAR**

Hambridge Road, Newbury, Berkshire, RG14 5TS. ENGLAND  
Tel: 01635 811500 Fax: 01635 811501 E-Mail: mastergear@oml.co.uk



To BS308

DIMENSIONS  
IN  
MM [INCHES]

DATE	14FEB02
DRAWN	JDH
CHECKED	PAB
SCALE	1:5

This drawing/design is the property of OPPERMAN MASTERGEAR Ltd. © and must not be used or copied without their specific written consent

DRG No. ME-15364

REV. A