ACTUATOR TYPE - M07 PADLOCK FLANGE



GENERAL INFORMATION

TRAVEL.....90° ±5° AT BOTH ENDS	MAX. OUTPUT TORQUE (1000 CYCLES)..2640 IN-LBS
RATIO.....40:1	MAX. OUTPUT TORQUE (5000 CYCLES)..2200 IN-LBS
TURNS TO CLOSE.....10	MAX. INPUT TORQUE (1000 CYCLES).....240 IN-LBS
MECHANICAL ADVANTAGE..11.0 ±10%	MAX. INPUT TORQUE (5000 CYCLES).....200 IN-LBS

MOUNTING HOLE DETAIL: (MSS SP-101)
PREFERED....FA07 (4 X 5/16-18 ON 2.75 BCD)
MAXIMUM.....FA07 (4 X 5/16-18 ON 2.75 BCD)
MINIMUM .....FA05 (4 X 1/4-20 ON 2.00 BCD)

APPROXIMATE WEIGHT.....7.0 LBS. (2.6 KG) (EXCLUDING HANDWHEEL)

MASTERGEAR
A REGAL BELOIT COMPANY
5466 EAST ROCKTON RD. • SOUTH BELOIT, IL 61080

DIMENSIONS IN INCHES	SCALE	DRAWING No.
	1:2	M07PL
	APPROVED BY NJC	REV.B 10/10/06

THIS PRINT IS CONFIDENTIAL AND IS THE PROPERTY OF MASTERGEAR. THIS PRINT SHALL NOT BE USED, COPIED OR REPRODUCED IN WHOLE OR IN PART NOR SHALL THE CONTENTS BE REVEALED IN ANY MANNER TO ANYONE UNLESS WRITTEN PERMISSION IS OBTAINED FROM MASTERGEAR. ©