

TRAVEL 90° ±5° AT BOTH ENDS
 RATIO 183:1
 TURNS TO CLOSE 45.75
 MECHANICAL ADVANTAGE ... 57 ±10%

MAXIMUM OUTPUT TORQUE (1000 CYCLES)..... 8000 Nm
 MAXIMUM OUTPUT TORQUE (5000 CYCLES)..... 6600 Nm
 MAXIMUM INPUT TORQUE (1000 CYCLES)..... 140 Nm
 MAXIMUM INPUT TORQUE (5000 CYCLES)..... 115 Nm


MOUNTING HOLE DETAIL (BSENISO 5211:2001)
 PREFERRED F25 (8 x M16 on 254 PCD)
 MAXIMUM F25 (8 x M16 on 254 PCD)
 MINIMUM F16 (4 x M20 on 165 PCD)

APPROXIMATE WEIGHT 44.5 kg



OPPERMAN MASTERGEAR

Hambridge Lane, Newbury, Berkshire, RG14 5TS. ENGLAND
 Tel: 01635 811500 Fax: 01635 811501 E-Mail: sales@opperman-mastergear.co.uk



DIMENSIONS IN
 MM [INCHES]

DATE	02Feb04
DRAWN	PAB
CHECKED	MAB
SCALE	1:5

This drawing/design is the property of OPPERMAN MASTERGEAR Ltd. © and must not be used or copied without their specific written consent. Specifications may change without prior notification

DRG No. ME-15308

REV. E