

TRAVEL 90° ±5° AT BOTH ENDS
 RATIO 1219.8:1
 TURNS TO CLOSE 304.95
 MECHANICAL ADVANTAGE ... 384.6 ±10%

MAXIMUM OUTPUT TORQUE (1000 CYCLES)..... 50000 Nm
 MAXIMUM OUTPUT TORQUE (2500 CYCLES)..... 41670 Nm
 MAXIMUM INPUT TORQUE (1000 CYCLES)..... 130 Nm
 MAXIMUM INPUT TORQUE (2500 CYCLES)..... 108 Nm

MOUNTING HOLE DETAIL (BSENISO 5211:2001)


APPROXIMATE WEIGHT 294.3 kg

PREFERRED F48 (12 x M36 on 483 PCD)
 MAXIMUM F48 (12 x M36 on 483 PCD)
 MINIMUM F25 (8 x M16 on 254 PCD)



OPPERMAN MASTERGEAR

Hambridge Lane, Newbury, Berkshire, RG14 5TS. ENGLAND
 Tel: 01635 811500 Fax: 01635 811501 E-Mail: sales@opperman-mastergear.co.uk



DIMENSIONS IN
 MM [INCHES]

DATE	25Apr06
DRAWN	TK
CHECKED	BJH
SCALE	1:8

This drawing/design is the property of OPPERMAN MASTERGEAR Ltd. © and must not be used or copied without their specific written consent. Specifications may change without prior notification

DRG No. ME-15450

REV. A